1

2 **Compensating for Color Response and Transfer Function of**

3 **Scanner and/or Printer When Reading a Digital Watermark**

4

5 **<u>Related Applications:</u>**

6 Priority is claimed based upon co-pending application 60/173,880 filed 12/31/00

7

8 **<u>Field of the Invention:</u>**

9 The present invention relates to steganography and more particularly to reading digital

10 watermarks.

11

12 **<u>Background of the Invention:</u>**

13 The technology for inserting digital watermarks in digital images and for reading digital

14 watermarks from digital images is well developed. There are many issued patents and

15 published technical papers which explain the technology for reading watermarks.

16

17 Frequently after a digital watermark has been inserted into a digital image, the image is

18 printed and later the printed image is scanned to create a new digital image. However,

19 printers and scanners do not precisely reproduce images. That is, printers and scanners

20 introduce anomalies, distortions and changes into an image as it is being printed or

21 scanned. The typical operations which are performed on watermarked images are

22 illustrated in Figures 1A and 1B.

23

24 The process begins with a digital image 10A. An image editing program 11 is used to

25 insert a digital watermark into the image. For example a watermark may be inserted into

26 the image 10A by the watermark program which is part of the commercially available

27 image editing program marketed by Adobe Corporation under the trademark "Adobe

28 Photoshop". Next, a printer 12 is used to create a physical image 10B which includes a

29 digital watermark.

30

31 Next as illustrated in Figure 1B, the physical image 10B is passed through a scanner 13

32 to generate a digital image 10C. The digital image is then processed by a watermark

33 detection program 14 to detect the watermark. For example the watermark may be

1   detected by the watermark detection program which is part of the commercially available

2   image editing program marketed by Adobe Corporation under the trademark "Adobe

3   Photoshop".

4

5   Printer 12 and the scanner 13 generally do not have a perfect color response and they

6   have transfer functions which is other than unity. That is, they introduce anomalies,

7   distortions or changes into the image. For example, with some scanners, if a printed

8   image is scanned and then displayed, the appearance of the displayed image will not be

9   identical appearance to the hard copy image. Likewise, with some printers, if a digital

10   image is printed, the printed image will not appear to be identical to a display of the

11   original digital image. As used herein the term scanner is used to mean conventional

12   flatbed and sheet feed scanners as well as other image acquisition devices such as

13   digital cameras. Anomalies, distortions or changes introduced into an image by a printer

14   or scanner are hereinafter collectively referred to as "artifacts". Such artifacts may

15   interfere with the operation of the watermark detection program 13 or with programs

16   used to detect patterns or geometric shapes in an image.

17

18   Some watermark or pattern detection programs compensate for scale and rotation of an

19   image. However, the prior art watermark and pattern detection programs do not

20   adequately compensate for artifacts introduced into an image by a printer or scanner.

21   Such artifacts can make detection of a digital watermark or pattern difficult if not

22   impossible. This is particularly true when such artifacts are coupled with other changes

23   such as scaling, rotation and wear and tear.

24

25   **Summary of the Invention:**

26   Watermark and pattern detection can be improved by compensating for artifacts

27   introduced into an image by a printer and/or scanner through which the image has

28   passed. With the present invention, prior to watermark or pattern detection, the image is

29   filtered or modified to compensate for artifacts introduced by the printer and/or scanner.

30

31   Some scanners automatically compensate for artifacts introduced by the scanner by

32   using a calibrated tone map. The automatic compensation provides an image from

33   which, a watermark can be easily read. However, generally the user is provided with an

1   interface which can be used to change certain parameters such contrast and intensity.

2   The changes made by the user change the compensation (i.e. the tone map) applied to

3   the image. If the user changes the compensation applied to the image it can affect the

4   ability to read the watermark. The present invention provides a system which reverses

5   any compensation introduced by the user so that the watermark or pattern can be more

6   easily read.

7

8   In another embodiment the invention takes into consideration that some printers and

9   scanners have transfer functions which differ in the "x" and "y" directions. Thus the

10 compensation introduced by the filter can differ in the "x" and "y" directions. In one

11 embodiment, a scanner introduces aliasing frequencies into an image. Detection is

12 improved by selectively removing certain frequencies. In another embodiment, the filter

13 compensates for fact that the scanner frequency response falls off at higher frequencies.

14

15 **Brief Description of the Figures:**

16 Figures 1A and 1B show the process used in the prior art.

17 Figure 2 illustrates a preferred embodiment of the invention using TWAIN interface.

18 Figures 3A and 3B are flow diagrams illustrating the operation of the present invention.

19 Figure 3C shows the change in Gamma curve due to user setting.

20 Figures 4A and 4B show the process used in an alternate embodiment of the present

21   invention.

22 Figure 5A, 5B and 5C are used to describe an alternate embodiment of the invention.

23 Figure 6 illustrates a technique for detecting the transfer function of a scanner and

24   printer.

25

26 **Detailed Description of embodiments of the invention:**

27 The preferred embodiment of the invention described herein utilizes the invention to

28 facilitate detecting and reading a digital watermark from an image. As explained later,

29 the invention can also be used to facilitate the operation of other types of image analysis

30 programs such as programs that detection geometric shapes, logos or other patterns. It

31 is also noted that the preferred embodiment utilizes a scanner as an image acquisition

32 device. Other types of image acquisition devices such as digital cameras could also be

33 used with the present invention.

1

2　The first preferred embodiment of the present invention is shown in Figure 2.　The

3　system shown in Figure 2 includes a computer 30 and a scanner 24. In the particular

4　embodiment described herein the scanner 24 is the Hewlett-Packard ScanJet model

5　6300c scanner (hereinafter HP 6300).　The computer 30 can be a personal computer

6　operating under the Microsoft Windows operating system.

7

8　The computer 30 includes an application program 21, and a watermark reading program

9　26.　The application program 21 may, for example, be an image editing program such as

10　"Adobe Photoshop" which is marketed by Adobe Corporation of San Jose California.

11　The watermark reading program 26 may for example be similar to the watermark reading

12　program which is included as a part to the Adobe PhotoShop program; however,　as

13　used here the watermark reading program 26 is separate from the application program

14　21.

15

16　The HP 6300 scanner uses what is known in the art as a "TWAIN" interface.　The

17　application program 21 is connected to a scanner 24 using a TWAIN interface 20.　The

18　TWAIN interface was developed by the TWAIN Working Group and it provides a

19　standard software protocol and application programming interface (API) that regulates

20　communication between software applications and imaging devices such as scanners.

21

22　Two key elements in a system that uses the TWAIN interface are the source manager

23　software and the data source software.　These elements are described in detail in the

24　TWAIN specification which is available on the Internet at a site maintained by the TWAIN

25　organization.　This site can be located by doing an Internet search under the name

26　TWAIN.　The TWAIN specifications version 1.9 as ratified by the TWAIN working group

27　on January 20, 2000 is hereby incorporated herein by reference.

28

29　As shown in Figure 2, the system includes data source manager software 22 data

30　source software 23.　The data source manager software 22 is a widely available

31　program which provides an interface to a wide variety of imaging devices.　The data

32　source program 23 and the application program 21 have a TWAIN compliant interface to

33　the data source manager 22.　The data source program 23 provides a hardware

1   dependent connection to the scanner 24. The HP 6300 is provided to users with a data

2   source program which has a user interface, a TWAIN interface and a hardware interface

3   to scanner 24. It should be appreciated that the invention can be applied to a large

4   number of similar scanners. The present invention provides a modified data source

5   program 23. Only those parts of the data source program 23 that are relevant to the

6   present invention will be described herein. The remaining parts of the data source

7   program 23 are conventional.

8

9   The data source software 23 communicates with the scanner 24 using a Scanner

10   Control Language (SCL). This SCL language is described in a manual entitled "Scanner

11   Control Language (SCL) and C Language Library for Hewlett-Packard Scanners v 11.0"

12   which is published and distributed by Hewlett-Packard Corporation. This manual is

13   hereby incorporated herein in its entirety and is hereinafter referred to as the scanner

14   SCL Manual. Only those parts of data source program 23 that are relevant to the

15   present invention are described herein.

16

17   A user interface provided by data source program 23 allows a user to change the tone

18   and contrast of the image produced by scanner 24. The present invention is directed to

19   insuring that changes made by the user do not interfere with the operation of the

20   watermark detection program 26.

21

22   The scanner 24 includes a mechanism for providing a Gamma correction to the scanned

23   image. The Gamma correction curve (i.e. an adjustment for the luminosity of each pixel

24   in a scanned image) is controlled by a tone map which can be downloaded into the

25   scanner by the data source program 23. In the scanner 24, the RGB values for each

26   pixel are first adjusted in accordance the values in a 3 by 3 matrix which adjusts each

27   color based on the values of the other colors of that pixel. Next the luminance value of

28   each pixel is adjusted in accordance with a Gamma curve that specifies an adjustment

29   for each particular luminance value. The term tone map as used herein refers to the

30   values for the 3 by 3 matrix and the values which specify an appropriate adjustment for

31   each luminance value (that is, the Gamma curve).

32

33

1   In the following discussion reference will be made to the following three tone maps:

2   1) Default tone map: a tone map stored in the printer that is used to adjust an

3   image if no other tone map is provided to the printer.

4   2) Calibrated tone map: a tone map which is generated from a test pattern and

5   which is designed to produce, in so far as possible, a true digital

6   representation of the scanned image. As used herein, the term a true

7   digital representation means a digital image which when displayed

8   appears identical to the original printed image that was scanned. A

9   technique for generating a calibrated tone map is described later with

10   reference to Figure 3B.

11   3) User adjusted tone map: a tone map which is generated in response to user

12   input to change an image so that the image has the contrast and intensity

13   requested by the user.

14

15   The data source program 23 provides a conventional user interface through which a

16   user can change the contrast and intensity of a scanned image. When a user changes

17   the desired contrast and intensity of an image, the calibrated tone map is changed into

18   the user adjusted tone map so that the image will have the user specified characteristics.

19   This is a conventional operation which is preformed by the data source program that is

20   provided with the HP6300 scanner.

21

22   When an image is scanned, the resulting digital data, corrected in accordance with the

23   user adjusted tone map, is sent to the application program 21. The data is also sent to

24   an inverse user adjustment program 25. The inverse user adjustment program 25

25   reverses any changes made to the image to satisfy the settings entered by the user.

26   The output of the inverse user adjustment program 25 is a digital image that is identical

27   to the digital image that would have been produced if the calibrated tone map had been

28   applied to the image instead of the user modified tone map. The image as changed by

29   inverse user adjustment program 25 is then sent to the watermark reading program 26.

30

31   The inverse user adjustment program 25 determines what changes were made to the

32   calibrated tone map as a result of inputs from the user. Inverse user adjustment

33   program 25 then applies the inverse of these changes to the image produced by

1   scanner 24.   The inverse user adjustment program 25 is a program that performs a

2   inverse table look up operation.   Programs to perform a inverse table look up are

3   conventional. The action performed by inverse user adjustment program 25 is illustrated

4   in Figure 3C. When a user adjusts the contrast setting, the shape of the Gamma curve

5   is changed. Figure 3C illustrates what happens to the Gamma curve when the user

6   adjusts the contrast of the image. In the example shown, the contrast

7   setting was lowered by the user. As a result of the changes by the user the Gamma

8   curve was changed and at the upper end (at higher intensity) the pixels are given a

9   lower intensity than prior to the adjustment. The inverse user adjustment program 25

10   reverses the delta created by the user settings.

11

12   The following example illustrates the what occurs when the calibrated tone map is

13   changed into a user adjusted tone map and how the inverse user adjustment program

14   25 operates.

15

16   Assume that the calibrated tone map has the following values (for convenience only a

17   small section of the tone map is give).

18

19   Calibrated tone map values:

Input values	251	252	253	254	255	256	257	258	259
output values	249	250	251	252	253	254	255	256	257

20

21   Let us assume that due to inputs from the user, the following user adjusted tone map is

22   generated (again only a small portion of the map is shown).

23

Input values	251	252	253	254	255	256	257	258	259
Output values	248	249	250	251	252	253	254	255	256

24

25   The inverse user adjustment program 25 would perform a reverse table look up as

26   follows:

27   When, for example, it receives a value of 256, it would perform a reverse table look in

28   the User Adjusted Tone map and determine that the 256 value came from an input value

29   of 259. It would then adjust this value to 257 as specified by the calibrated tone map.

1

2 The operation of the system is illustrated in Figures 3A and 3B. Figure 3A illustrates the

3 normal operations that occur when an image is scanned. Figure 3B illustrates the

4 operations that are used to generate a calibrated tone map and to initialize the system.

5 The operations shown in Figure 3A normally take place each time the scanner is used to

6 acquire an image. However, it should be noted that the operations illustrated in Figure

7 3A take place after a calibrated tone map has been generated and stored in the data

8 source 23 using the technique illustrated in Figure 3B. .

9

10 The operation of the system as illustrated in Figure 3A will now be explained. As

11 indicated by box 301 when a user wants to scan an image, the user sets the tone and

12 intensity controls (or indicates that the defaults settings should be used).   As indicated

13 by block 302, the calibrated tone map is then changed to produce a user adjusted tone

14 map (i.e. a tone map which will produce an image with the desired tone and intensity).

15

16 As indicated by block 303, the user adjusted tone map is sent to the scanner. As

17 indicated by blocks 304 and 305, the image is then scanned and the scanner applies the

18 user adjusted tone map to the digital data generated by the scanner.   The image

19 adjusted by the user adjusted image is herein termed an adjusted digital image.

20

21 As indicated by block 314, the adjusted digital image(i.e. the digital image with the user

22 adjusted tone map applied) is supplied to the inverse user adjustment program 25.

23 Program 25 reverses the changes made in the tone map to satisfy the user entered tone

24 and contrast setting.   The result is that inverse user adjustment program 25 produces a

25 corrected image adjusted according to the calibrated tone map. As illustrated in Figure

26 3C, the inverse user adjustment program 25 changes the image such that the result of

27 both the correction made in the scanner and the correction made by inverse user

28 adjustment program 25 (i.e. the sum of both corrections) is the same correction as would

29 have been made by the calibrated tone map if only it had been applied to the image.

30

31 As indicated by block 315 the system sends the corrected digital image produced by

32 inverse user adjustment program 25 to watermark reading program 26 which detects

33 and reads the watermark. The watermark reading program 26 may be a conventional

1 watermark reading program such as that which is a part of the commercially available

2 "Adobe PhotoShop" program.

3

4 The invention is directed to enhancing the ability to read a watermark. Once the

5 watermark is read, the data obtained can be used for a large variety of purposes. For

6 example, once the watermark is read, the data from the watermark can be merely

7 supplied to an operator or possibly to another program.

8

9 However, as indicated by dotted blocks 316, 321, 322 and 323, in one alternate

10 embodiment, the output of the watermark detector 29 controls what data is sent to the

11 data source manager 22 and to the application program 21. For example, if the

12 watermark detector reads certain data, such as the name of the copyright owner, the

13 name of the copyright owner along with the image corrected in accordance with the user

14 adjusted tone map may be sent to the application program 22. Alternatively, if a

15 different watermark is read, the image may not be sent to the application program. It

16 can for example be used accesses a particular web site on the internet in accordance

17 with the commercially available service market by Digimarc Corporation under the

18 trademark "MediaBridge".

19

20 In its simplest form the control indicated by block 316 can be implemented by a look up

21 table that indicates what operation should be performed depending upon what particular

22 watermark is detected. In the embodiment where the functions illustrated by blocks

23 316, 322 and 323 are performed, the transfer from data source 23 to data source

24 manager 22 would be controlled by a gating mechanism which would only transfer the

25 data from the scanner to the data source manager 22 and thus to the application

26 program 21 depending on the output of watermark reading program 26. Alternate

27 connections could be provided from data source manager 22 to other applications, again

28 dependent upon the output of watermark reading program 26.

29

30 In still another embodiment, the output of the inverse user adjustment program 25 is

31 both sent to a watermark reading program and to a shape recognition program. The

32 combined output from both of the watermark reading program and the shape recognition

33 program are then used to determine which operation should be taken.

1

2 Figure 3B illustrates how the scanner is initialized, how the calibrated tone map is

3 generated and how the user modified tone map is sent to the scanner. As initially

4 installed the system uses a default tone map as indicated by block 351. The default

5 tone map can be a very simple tone map with a straight line relationship between input

6 and output, that is, a straight line Gamma curve.

7

8 Next, a test pattern and a calibration program is used to generate the calibrated tone

9 map. The International Color Consortium has developed a standard color calibration

10 format. Information about the standard color calibration can be found on a web site

11 maintained by the Color Consortium. The web site has the name "color" and the group

12 designator "org" (note URLs are not permitted in a patent application but the URL can be

13 easily located from the above information)

14

15 The calibration technique uses a standard color calibration target to create a calibration

16 profile for the scanner. The scanner is calibrated so that when a color calibrated target

17 is scanned, the output will be a defined RGB output which faithfully reproduces the color

18 calibrated target. Thus two scanners from different manufacturers which have been

19 similarly calibrated will produce similar (if not identical) outputs from the same image.

20

21 As indicated by blocks 352 and 353, a test pattern is scanned and a test image is

22 generated using the default tone map. A calibrated tone map, (that is, a tone map

23 which would have produced an image which faithfully reproduced the test pattern) is

24 generated as indicated by block 354.

25

26 There are commercial programs available which can be used to generate the calibrated

27 tone map. A number of companies including Kodak, Fuji and ColorBlind Inc. provide

28 calibration packages. The packages can be used for calibrating scanners, printers and

29 monitors. Details of the calibration packages can be found at a web site maintained by

30 Kodak corporation and at a web site with the name "itec" and the group designator "net"

31 and at a web site with the name "ffei" and the designator "co.uk"

32

1   The calibrated tone map is stored in the data source program 23 as indicated by block

2   355. Next when a user wants to scan an image, the user may enter desired parameters

3   such tone and contrast. In the preferred embodiment, the parameters entered include

4   only tone and contrast; however, provision could be made to allow the user to adjust

5   other additional parameters. For example, the user could be allowed to set the other

6   color parameters such as hue, or the user could be allowed to set other parameters such

7   as X Resolution, Y Resolution, X Scale factor, Y Scale factor, etc.

8

9   The resolutions may be of particular interest, since if there are *differing* resolutions or

10 scale in the X and Y direction, it would be desirable to correct for this prior to attempting

11 to detect the watermark. Resolution may be important since some watermark detectors

12 cannot read watermarks if images have different resolutions in the X and Y direction.

13 Also, if scale differs more than a few percent in X and Y it may make reading the

14 watermark difficult. However, with the present invention if an image that has different

15 sample rates or scale applied in X and Y directions, these can be adjusted prior to the

16 watermark or pattern detection process.

17

18 Some scanners also have a "Set Filter" command for the scanner that controls how

19 several pixels in the X direction may be averaged together to create a smoothed image.

20 This command can be used to manually control the filtering. Also, some scanners have

21 an "Inquire Auto-Filtering" command that lets the software ask the scanner what filtering

22 in (in the X direction) is being used when the scan is done in the Auto-Filter mode. With

23 the present invention, an awareness of what type of spatial filtering is being done, and

24 the fact that it differs in the X and Y directions, could be used to either adjust and pre-

25 compensate prior to detection, or could affect the operation of the detection algorithms.

26

27 As indicated by block 357, a user modified tone map which will produce an image with

28 the desired characteristics is generated. The technique for generating a calibrated tone

29 map from a test pattern and for altering a calibrated tone map in accordance with user

30 entered parameters is known in the art. A "driver" which modifies a calibrated tone map

31 in accordance with user entered parameters is provided by the manufacturer with many

32 commercially available scanners. Finally as indicated by block 358, the user modified

1   tone map is sent to the scanner and the process proceeds as indicated in block 303 in

2   Figure 3A.

3

4   The preferred embodiment of the invention described above relates to enhancing the

5   operation of a watermark detection program. The invention could be similarly applied to

6   enhancing the operation of programs such as programs the detect geometric shapes

7   such as logos or particular patterns in an image. Likewise the invention could be applied

8   to enhancing the operation of feature extraction programs, such as program for face

9   recognition, fingerprint detection etc. In all these cases the inverse user adjustment

10 program 25 would reverse any changes made as a result of settings entered by the user.

11

12 In embodiments that use shape or image recognition the watermark detection program

13 26 would be replaced by an image or shape recognition program. Alternatively, a shape

14 or image recognition program could be provided in addition to watermark detection

15 program 26 and the output from both such programs would determine the action taken

16 by control block 316.

17

18 In an alternate embodiment of the invention, a special tone map is developed with the

19 specific object of enhancing the ability to read a watermark and to detect shapes in a

20 digital image which has been scanned. This special tone map is developed in order to

21 reverse artifacts introduced into an image by a scanner. The special tone map is then

22 either directly applied to the image generated by a scanner or the user adjustment

23 program reverses any changes made to the image that differ from the values in the

24 special tone map.

25

26 An overall flow diagram for an alternate embodiment of the invention is shown in Figures

27 4A to 5D. The embodiment shown in Figures 4A to 5D, takes into consideration the fact

28 that the transfer function of a printer or scanner may differ in the x and y directions. The

29 process begins with a digital image 420A. A watermark is introduced into the image by a

30 watermarking program 421. The watermarking program 421 may for example be the

31 commercially available program "Adobe PhotoShop" which is marketed by the Adobe

32 Corporation. The watermarked image is then printed by a printer 422 resulting in a

33 watermarked physical image 420B

1

2   The image 420B is next passed through a scanner 423 to generate a digital image 420C

3   as illustrated in Figure 4B. The scanner 423 has a transfer function S(u,v) where "u" and

4   "v" are the horizontal and vertical frequency axis. Of particular importance is the fact

5   that the transfer function of scanner 423 differs in the "x" and "y" directions.

6   Furthermore, the transfer function of the scanner is separable in the "u" and "v"

7   dimensions and the transfer function S(u,v) can be represented as S(u) times S(v).

8

9   The image 420C is passed through (or operated upon by) a transfer function 425 which

10   approximates as close as possible the inverse of the transfer function S(u). The image

11   is passed through (or operated upon by) a transfer function 426 which approximates as

12   close as possible the inverse of the transfer function S(v). Both of the operations 425

13   and 426 may be done simultaneously. The technique for designing a filter with a

14   particular transfer function is well know. The result of passing the image through filters

15   425 and 426 is a modified digital image 420D. The modified digital image 420D is then

16   passed through a conventional watermark detection program 424 in order to detect the

17   watermark.

18

19   While the above embodiment relates specifically to compensating for anomalies

20   introduced by scanner 423, the filters 425 and 426 could likewise be designed to

21   compensate for anomalies introduced by the transfer function of the printer 422 or for

22   both the transfer functions of printer 422 and scanner 423.

23

24   The second embodiment of the invention described above relates to the use of filters

25   which approximate as close as possible the inverse of the transfer function of a scanner.

26   Such filters of necessity will be relatively complex. A simpler embodiment of the

27   invention is illustrated in Figures 5A to 5D.

28

29   With reference to Figures 5A to 5D, it is specifically noted that an image has a two

30   dimensional frequency spectrum. For convenience in illustration, Figures 5A to 5C show

31   one dimensional frequency spectra. That is, the frequency spectrum of an image is in

32   fact two dimensional; however, the principles can be more conveniently illustrated with a

33   diagram that shows a one dimensional frequency spectrum. Hence, Figures 5A to 5D

1   show one dimensional spectra; however, it should be understood that in fact they merely

2   illustrate one dimension of a two dimensional spectrum.

3

4   A scanning process is of necessity a sampling process. As is well know, a sampling

5   process produces a periodic frequency spectrum. If sampling is at a frequency F_s the

6   spectra are separated by F_s as shown in Figure 5A. If the sampling frequency is too low,

7   the frequency spectra will overlap as shown in Figure 5C.

8

9   In the case where the spectra do not overlap such as shown in Figure 5A, the

10   compensating transfer functions 425 and 426 are designed to enhance the lower

11   frequency components of the signal so that the spectra are relatively square as shown

12   by spectra P1m to P3m in Figure 5B.

13

14   In the situation where the scanner resolution (i.e. for example, the scanner sampling

15   frequency in the X direction) produces a frequency spectrum such as that shown in

16   Figure 5C, the watermark detection can be improved by filtering out frequency ranges A

17   and B which are shown in Figure 5D. That is, the compensating transfer function of filter

18   225 shown in Figure 4B would be a simple frequency filter which eliminates the

19   frequency in ranges A and B shown in Figure 5C.

20

21   Any printers and any scanner has a transfer functions which is particular to the particular

22   physical characteristics of the printer. In general the manufacturer of a printer or a

23   scanner would best understand the transfer function of a particular printer or scanner.

24   However, if the transfer function of a printer or a scanner can not be obtained from the

25   units manufacturer, it can be determined experimentally. The transfer function of a

26   printer and of a scanner can be determined experimentally in various known ways. One

27   particular technique for determining the transfer function of a printer or of a scanner is

28   shown in Figure 6. First, a process for determining the transfer function of a scanner

29   642 will be described.

30

31   As illustrated in Figure 6, the process for experimentally determining a transfer function

32   of scanner 642 begins with a digital image 640A. The image 640A should be printed on

33   a very high quality printer to produce a physical image 640B which as closely as

1   possible is identical to image 640A. The physical image 640B is then scanned by

2   scanner 642 to produce a modified digital image 640C.

3

4   Next the original digital image 640A is compared to the modified digital image 640C by a

5   comparison program 643. Any differences between images 640A and 640C represent

6   anomalies introduced by the scanner 642. Stated differently the image 640C is image

7   640A modified by the transfer functions of scanner 642. In a practical situation, dozens

8   if not hundreds of images will be passed through the process shown in Figure 6 in order

9   to determine, as closely as possible, the transfer function of a particular scanner.

10

11 If one wants to determine the transfer function of a printer, a very high quality scanner

12 can be used in the process illustrated in Figure 6. In such a case differences between

13 images 640C or 640A would due to anomalies introduced by the printer.

14

15 It is noted that instead of using a very high quality printer or scanner as described above,

16 one could use a printer with a known characteristic when seeking to determine the

17 transfer function of a scanner and one could use a scanner with a known transfer

18 function when seeking to determine the transfer function of a printer. The known

19 transfer function of the printer or scanner would then be taken into account when

20 seeking to determine the transfer function of the other component.

21

22 The differences detected by comparison program 643 can be used to generate a

23 function or filter that approximates the inverse of the transfer function of a printer 641 or

24 of a scanner 642 or the differences can be used to design a compensating filter as used

25 in the embodiment described with reference to Figures 5A to 5D. The differences in the

26 "x" and "y" directions can be processed separately in order to be able to separately

27 compensate for the differences in the x" and " y" directions.

28

29 While the invention has been described with respect to a number of different

30 embodiments of the invention, it will be understood by those skilled in the art that various

31 changes in forma and detail can be made without departing from the spirit and scope of

32 the invention.

33